SONY



3LCD Laser Projector



Why Sony?

Sony is an industry leader in the world of imaging technology, across both consumer and professional applications.

Our comprehensive imaging technologies extend across a wide range: lenses, image sensors, image processors, IP transmission, display devices and light sources. Products are developed by engineers with deep and broad experience in imaging technologies.

As a leading global manufacturer for professional users, Sony offers superlative movie-making and broadcast equipment, as well as medical technologies and business and educational products.




Image quality




Sony's BrightEra™ 3LCD panel works with Sony's original Z-Phosphor™ light source to deliver unmatched clarity, color reproduction and smooth gradation.

Sony's 'Reality Creation' engine delivers ultra-high accuracy by combining database-driven, super-resolution processing with image pattern classification. Automatic control of both super-resolution processing and noise reduction ensures stunning image quality, smooth gradations and low noise.



Intelligent setting



Intelligent Settings offer four presets, optimising brightness, cooling system and other projector settings to suit all usage environments.

In addition, VPL-FHZ131L, VPL-FHZ101L, VPL-FHZ91L, VPL-PHZ60, and VPL-PHZ50 are equipped with an Advanced Intelligent Setting function,

which automatically control the temperature of the installation environment, frequency of usage, and several other parameters so that they can be used at suitable settings for long-term stable operation.

Simple and discreet

The projector's minimalist design looks great in any space, blending seamlessly into the background of conference rooms, museums, and other sophisticated locations

An experienced team of designers have created a functional, aesthetically pleasing product that is durable, easy to set up, and easy to use.



3LCD laser projector lineup, by venue

	nue	Large Halls, Auditoriums 13,000 Im	Museums, Galleries 10,000 Im	Bright classrooms, Meer			
Bright	itness	13,000 IIII		9,000 IIII			
Model	l name	VPL-FHZ131L	VPL-FHZ101L	VPL-FHZ91L			
Lens shift (Maximum)	Vertical	±107%					
	Horizontal	±57%					
Lens				Interchal			
Throw			Depends on lens				
	lution			40" + 600"			
Scree	n size	407614	40" to 600"				
Power consumption (Maximum)	AC 100 V to 120 V	1076 W	840 W				
	AC 220 V to 240 V	1033 W	814	4 W			
	Power requirements			(
	protrusions) & weight	Approx. 544 x 205 x 564 mm (27 kg)	Approx. 544 x 205 x 564 mm (26 kg)				
	output		DVI-D HDMI HDBaseT 3G-SDI	Output PC/Component 3G-SDI			
	input / output		RS-232C LAN USB A				
	creation		•	•			
	nt setting	Version 2	Version 2	Version 2			
Automatic fi	ilter cleaning	•	•	•			
Edge b	lending	•	•	•			
War	ping	•	•	•			

^{*1:} support as an option, required BKM-PJ20

Optional lenses

For VPL-FHZ131L/FHZ101L/FHZ91L

Model name	VPLL-Z4107	VPLL-4008	VPLL-Z4111	VPLL-Z4015	VPLL-Z4019	VPLL-Z4025	VPLL-Z4045	
Throw ratio	0.75:1 to 0.94:1	1.00:1	1.30:1 to 1.96:1	1.85:1 to 2.44:1	2.41:1 to 3.07:1	3.02:1 to 5.58:1	5.56:1 to 7.5:1	
Zoom	Powered	-	Powered Powered		Powered	Powered	Powered	
Focus	Powered	Manual	Powered	Powered	Powered	Powered	Powered	
Screen size	60" to 600"	40" to 600"	60" to 600"	40" to 600"	40" to 600"	40" to 600"	60" to 600"	
Lens shift (V, H)	shift (V, H) ±50%, ±24% ±32%, ±15% ±99%, ±		±99%, ±51%	±98%, ±51%	±107%, ±57%	±107%, ±57%	±107%, ±57%	
Weight	Weight 3.3 kg 2.6 kg		4.0 kg	3.0 kg	3.0 kg	2.8 kg	3.0 kg	

^{*2:} VPL-PHZ60, VPL-PHZ50 and VPL-CWZ10 do not support correcting deflection

Small ting rooms, Large rooms Mid-sized rooms SOHO 6,500 lm 5,500 lm 6,000 lm 5,000 lm 5,000 lm VPL-FHZ75 VPL-FHZ70 VPL-PHZ60 VPL-PHZ50 VPL-CWZ10 -5%, +70% -35% to +55% N/A (Lens Offset Vertical +37%) ±32% ±15% Fixed ngeable 1.39:1 to 2.23:1 (When using the included lens) 1.23:1 to 1.97:1 1.29:1 to 2.07:1 WUXGA (1920 x 1200) WXGA (1280 x 800) 40" to 300" 537 W 483 W 440 W 342 W 518 W 468 W 418 W 326 W AC 100 V to 240 V Approx. 460 x 169 x 515 mm (16 kg) Approx. 422 x 100 x 333 mm (7 kg) Approx. 422 x 100 x 333 mm (6.6 kg) Approx. 371 x 100 x 319.3 mm (5.7 kg)

	•		•		•			-			
	Version 1		Version 1		Version 2				Version 1		
	•		•				-				-
	•		•		-					-	
	•		•				● *2				● *2
O BNC	D-sub 15 pin	O RCA	DVI-D	— НС	OMI [T RJ-45	D-sub 9 pin	Stereo mini jack	U:	SB A	USB for power supply

Audio HDBaseT Video

USB A USB for power supply

Output Output Audio

Input PC HDMI Audio Video Output Audio

For VPL-FHZ75/FHZ70

Input Video PC DVI-D HDMI Audio HDBaseT Output PC DVI-D Audio

LAN IR (Control S) input

Model name	VPLL-3003	VPLL-3007	VPLL-Z3009	VPLL-Z3010	VPLL-Z3024	VPLL-Z3032	
Throw ratio	0.33:1	0.65:1	0.85:1 to 1.0:1	1.0:1 to 1.39:1	2.34:1 to 3.19:1	3.18:1 to 4.84:1	
Zoom	-	-	Manual	Powered	Powered	Powered	
Focus	Powered	Manual	Manual	Powered	Powered	Powered	
Screen size	80" to 300"	60" to 300"	60" to 300"	60" to 300"	40" to 600"	40" to 600"	
Lens shift (V, H)	±5%, ±5%	+10%/-5%, +/-4%	+50%/-5%, ±24%	+60%/-5%, +/-29%	+60%/-5%, +/-32%	+60%/-5%, +/-32%	
Weight 2.9 kg		1.7 kg	1.7 kg	2.0 kg	1.2 kg	1.2 kg	



VPL-FHZ131L 13,000Im, WUXGA
VPL-FHZ101L 10,000Im, WUXGA
VPL-FHZ91L 9,000Im, WUXGA

- Installation flexibility
 - Very wide range of lens shift adjustment and a wide choice of interchangeable lenses including VPLL-Z4107 short throw lens
- Networked control and monitoring
 - Ideal for integration in AV environments with leading control, monitoring and management systems such as Crestron Connected® and Extron® XTP™ Systems.*
 - * Extron and XTP Systems are trademarks of RGB Systems Inc.



VPL-PHZ60 6,000Im WUXGA VPL-PHZ50 5,000Im WUXGA

- Bright View
 - Bright View delivers easy-to-see images, even in bright environments
- Installation flexibility
 - Enjoy easy installation and greater flexibility with lens shift to position the projector in higher spaces
 - Supports for 4K 30P input signals and wide range of major control interfaces
- Networked control and monitoring
 - Ideal for integration in AV environments with leading control, monitoring and management systems such as Crestron Connected® and Extron® XTP™ Systems.*
 - * Extron and XTP Systems are trademarks of RGB Systems Inc.



VPL-CWZ10 5,000Im, WXGA

- Affordable 3LCD laser projector
 - Quick power on/off
 - Consistent brightness
 - Reduced maintenance
- Lightweight, compact blend-in design

SONY

https://pro.sony/projectors

©2020 Sony Home Entertainment & Sound Products Inc.

 $Reproduction\ in\ whole\ or\ in\ part\ without\ written\ permission\ is\ prohibited.$

 $\label{prop:continuous} Features \ and \ specifications \ are \ subject \ to \ change \ without \ notice.$

The values for mass and dimension are approximate.

"SONY" is a registered trademark of Sony Corporation.

"Z-Phosphor" and "BrightEra" are trademarks of Sony Corporation.

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.

 ${\sf HDBaseT^{\sf TM}} \ and \ the \ {\sf HDBaseT} \ Alliance \ logo \ are \ the \ trademarks \ of \ the \ {\sf HDBaseT} \ Alliance.$

Crestron Connected is trademarks of Crestron Electronics, Inc.

 $\label{eq:All other trademarks} All other trademarks are the property of their respective owners.$

Please visit Sony's professional website or contact your Sony representative for specific models available in your region.

HESMK0002V1YIT20NOV

Distributed by